



WARRANTY

This warrants that all MAXX Floor™ resilient products, as shown above, will be free from defects in materials and workmanship for a specified period from date of invoice, provided that the warranty set forth shall apply only if such products are installed and maintained in accordance with the written instructions published by MAXX Flooring. Warranty shall be voided if such products are removed from the site of their original installation.

Collection	Residential (Wear, Fade, or Stain)	Commercial (Wear, Fade, or Stain)
Glue Down 6-mil	10	N/A
Glue Down 8-mil	12	6
Glue Down 12-mil	15	12
Glue Down 20-mil	Lifetime	Lifetime
Loose Lay 12-mil	15	10
Loose Lay 20-mil	Lifetime	Lifetime
WPC Click 12-mil	15	10
WPC Click 20-mil	Lifetime	Lifetime

TERMS WITHIN ONE YEAR: if a defect covered by this warranty is reported to MAXX Floors™ (a brand of the Davati Group) within one year of purchase, we will supply new material of similar color, pattern and quality to replace the defective material; WITHIN TWO YEARS: if a defect covered by this warranty is reported to the Davati Group, we will provide material of similar color, pattern and quality to replace the defective material.

Warranty Actioning:

MAXX Floors™ may require inspection of any claims, and request photographs and samples before approving claims. All our Flooring Products are warranted against manufacturing defects, improper wear, fade or stain acceptance that would result in loss of original pattern and color, under normal use and maintenance, from the date of purchase through the specified times stated in this warranty. Products must be installed and maintained according to the MAXX Flooring Installation & Maintenance Instructions to be covered by this Limited Warranty.

Upon receipt by of the above information, arrangements will be made for a Davati representative to inspect the material believed to be defective.

Warranty Exclusions:

- Damage caused by improper storage and handling before installation
- The material utilized for other than prescribed use as flooring, or otherwise deemed appropriate.
- Material installed with obvious defects
- Conditions resulting from installing, utilizing and maintaining flooring not in conformance with MAXX™ Floors Installation Instructions for Installing Interior Flooring Products – most current edition at the time of installing.
- Material not installed with adhesive proper for the flooring specified or for the job site conditions and intended use.
- Material not maintained according to MAXX™ Floors recommended maintenance procedures.
- Heavy Wheeled Traffic
- Situations created by and resulting from excessive moisture, alkali or hydrostatic pressure, mold and mildew in the substrate.
- Situations created by and resulting from flooding, standing water, and temperature extremes.
- Telegraphing of adhesive trowel lines, joint lines, underlayment fasteners, etc. Situations created by or resulting from lack of or improper protective matting at entry ways, landings and pivot points.
- Damage Resulting from abuse including, scratches, burns, cuts, etc....
- Damages to the Sub Floor